



LAWRENCE  
LIVERMORE  
NATIONAL  
LABORATORY

UCRL-CONF-234121

# Extension of the operating parameters of the two stage light gas gun to velocities below 2 km/sec.

R. S. Thoe

August 29, 2007

58th meeting of the Aeroballistic Range Association  
Las Cruces, NM, United States  
September 17, 2007 through September 20, 2007

## **Disclaimer**

---

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

## Extension of the operating parameters of the two stage light gas gun to velocities below 2 km/sec.

Robert S Thoe  
Lawrence Livermore National Laboratory  
Livermore, Ca 94550

The Joint Actinide Shock Physics Experimental Facility (JASPER) located in area 27 at the Nevada Test Site Has been tasked with providing high accuracy information on the Equation Of State (EOS) and other dynamic properties of weapons grade plutonium and other actinides important to the stockpile stewardship program. In the past 5 years this facility has provided dozens of experimental data points for the accurate determination of pressure density relationship for these materials over a broad pressure range. In order to complete this survey it is necessary to extend the low pressure region to include projectile velocities below 2 km/s.

For most gas gun facilities this would present not too great a difficulty, one could simply decrease the amount of propellant along with a decrease in the strength of the petal valve, However JASPER requires that the piston be securely embedded in the Acceleration Reservoir (AR) as part of the containment system. The projectile must remain flat and undistorted. This requirement makes the attainment of slow velocities problematic.

This talk will discuss the JASPER Facility, A finite difference code developed to give predictive capability for two stage gas guns, and a set of experiments performed to demonstrate this capability.

This work was performed under the auspices of the U.S. Department of Energy by University of California Lawrence Livermore National Laboratory under contract No. W-7405-Eng-48.